



Military-Fasteners.com

P/N 3M33-8-19A

Description

Fastener Length: 1-63/64", Thread: 1/2-20, Thread Length: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3M33819A
Minimum Qty (MOQ):	10 EA
NSN:	5306-00-011-2515
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N 3M33-8-19A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.781 Inches Minimum
Fastener Length:	1.953 Inches Minimum And 2.000 Inches Maximum
Head Height:	0.265 Inches Minimum And 0.297 Inches Maximum
Width Between Flats:	0.740 Inches Minimum And 0.752 Inches Maximum
Grip Diameter:	0.4986 Inches Minimum And 0.4991 Inches Maximum
Nominal Thread Diameter:	0.500 Inches
Grip Length:	1.188 Inches Nominal
Thread Quantity Per Inch:	20
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5735 Assn Std Single Material Response Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/3M33-8-19A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.