

P/N 3M707-3-5-5

Description

Fastener Length: 39/64", Thread: 10-32, Thread Length: 19/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: 3M707355

Minimum Qty (MOQ): 5 EA

NSN: 5305-01-030-9133

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N 3M707-3-5-5 Specifications

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	0.287 Inches Minimum And 0.337 Inches Maximum
Fastener Length:	0.609 Inches Minimum And 0.639 Inches Maximum
Head Style:	Oval Countersunk
Head Diameter:	0.297 Inches Minimum And 0.302 Inches Maximum
Grip Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Thread Quantity Per Inch:	32
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Comp Xm-13 Overall
Material Document And Classification:	Ams 5629 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/3M707-3-5-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/3M707-3-5-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/3M707-3-5-5 and selecting the quantity you want then click "add to cart".