

P/N 3M893-3-3

Military-Fasteners.com

Description

Fastener Length: 33/64", Thread: 10-32, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	3M89333
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-185-0566
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N 3M893-3-3 Specifications

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	0.313 Inches Minimum And 0.363 Inches Maximum
Fastener Length:	0.511 Inches Minimum And 0.541 Inches Maximum
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Screw Material:	Steel Comp E4340 Or Steel Comp 8740
Screw Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-6049 Mil Spec 2nd Material Response
Screw Surface Treatment:	Aluminum And Chromate
Screw Surface Treatment Document And Classification:	Mil-c-83488,type 2,class 3 Mil Spec Single Treatment Response
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/3M893-3-3</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.