

Description

Fastener Length: 41/64", Thread: 10-32, Thread Length: 25/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3M902C34A
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-238-3191
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N 3M902C3-4A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.380 Inches Minimum And 0.447 Inches Maximum
Fastener Length:	0.640 Inches Minimum And 0.687 Inches Maximum
Head Style:	Flat Countersunk Undercut
Head Diameter:	0.376 Inches Minimum And 0.381 Inches Maximum
Head Height:	0.032 Inches Minimum And 0.034 Inches Maximum
Shoulder Diameter:	0.2177 Inches Minimum First Shoulder And 0.2182 Inches Maximum First Shoulder
Shoulder Length:	0.240 Inches Minimum First Shoulder And 0.260 Inches Maximum First Shoulder
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Shoulder Shape:	Round First Shoulder
Special Features:	Furnish With One O-ring
Material:	Steel Comp Xm-13 Overall
Material Document And Classification:	Ams5629 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3M902C3-4A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.