



Military-Fasteners.com

P/N 3M902C3-8A

## Description

Fastener Length: 57/64", Thread: 10-32, Thread Length: 25/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	3M902C38A
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-285-7725
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc



\* See page 2 for technical characteristics

## P/N 3M902C3-8A Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.380 Inches Minimum And 0.447 Inches Maximum
<b>Fastener Length:</b>	0.890 Inches Minimum And 0.937 Inches Maximum
<b>Head Style:</b>	Flat Countersunk Undercut
<b>Head Diameter:</b>	0.3765 Inches Minimum And 0.3813 Inches Maximum
<b>Head Height:</b>	0.032 Inches Minimum And 0.034 Inches Maximum
<b>Shoulder Diameter:</b>	0.2177 Inches Minimum First Shoulder And 0.2182 Inches Maximum First Shoulder
<b>Shoulder Length:</b>	0.490 Inches Minimum First Shoulder And 0.510 Inches Maximum First Shoulder
<b>Internal Drive Style:</b>	High-torque
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Features Provided:</b>	Dry Film Lubricant And O Ring
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	1250000 Pounds Per Square Inch
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Shoulder Shape:</b>	Round First Shoulder
<b>Material:</b>	Steel Comp Xm-13 Overall
<b>Material Document And Classification:</b>	Ams5629 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3M902C3-8A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.