



Military-Fasteners.com

P/N 3M902C4-10A

Description

Fastener Length: 1-1/8", Thread: 1/4-28, Thread Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | 3M902C410A                                |
| Minimum Qty (MOQ):      | 1 EA                                      |
| NSN:                    | 5305-01-239-1515                          |
| Schedule B:             | 7318.15.2010                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N 3M902C4-10A Specifications

|  |   |
|--|---|
| <b>Thread Class:</b>                         | 3a  |
| <b>Thread Direction:</b>                     | Right-hand  |
| <b>Thread Length:</b>                        | 0.443 Inches Minimum And 0.510 Inches Maximum                                 |
| <b>Fastener Length:</b>                      | 1.078 Inches Minimum And 1.125 Inches Maximum                                 |
| <b>Head Style:</b>                           | Flat Countersunk Undercut   |
| <b>Head Diameter:</b>                        | 0.501 Inches Minimum And 0.506 Inches Maximum                                 |
| <b>Head Height:</b>                          | 0.058 Inches Minimum And 0.060 Inches Maximum                                 |
| <b>Shoulder Diameter:</b>                    | 0.2802 Inches Minimum First Shoulder And 0.2807 Inches Maximum First Shoulder |
| <b>Shoulder Length:</b>                      | 0.615 Inches Minimum First Shoulder And 0.635 Inches Maximum First Shoulder   |
| <b>Internal Drive Style:</b>                 | High-torque   |
| <b>Nominal Thread Diameter:</b>              | 0.250 Inches  |
| <b>Thread Quantity Per Inch:</b>             | 28  |
| <b>Minimum Tensile Strength:</b>             | 125000 Pounds Per Square Inch   |
| <b>Countersink Angle:</b>                    | 100.0 Degrees Nominal   |
| <b>Shoulder Shape:</b>                       | Round First Shoulder  |
| <b>Special Features:</b>                     | Furnish With One O-ring   |
| <b>Material:</b>                             | Steel Comp Xm-13 Overall  |
| <b>Material Document And Classification:</b> | Ams5629 Assn Std Single Material Response Overall                             |
| <b>Surface Treatment:</b>                    | Passivate Overall   |
| <b>Thread Series Designator:</b>             | Unjf  |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3M902C4-10A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.