

Description

Fastener Length: 1-3/16", Thread: 1/4-28, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3M902C411A
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-142-8409
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc

NO IMAGE
AVAILABLE

P/N 3M902C4-11A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.442 Inches Minimum And 0.509 Inches Maximum
Fastener Length:	1.140 Inches Minimum And 1.187 Inches Maximum
Head Style:	Flat Countersunk Undercut
Head Diameter:	0.502 Inches Minimum And 0.507 Inches Maximum
Head Height:	0.058 Inches Minimum And 0.060 Inches Maximum
Shoulder Diameter:	0.2802 Inches Minimum First Shoulder And 0.2807 Inches Maximum First Shoulder
Shoulder Length:	0.618 Inches Minimum First Shoulder And 0.640 Inches Maximum First Shoulder
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Countersink Angle:	100.0 Degrees Nominal
Shoulder Shape:	Round First Shoulder
Special Features:	Furnished With One Rubber O Ring
Material:	Steel Comp Xm-13 Overall
Material Document And Classification:	Ams5629 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3M902C4-11A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.