

Description

Fastener Length: 13/16", Thread: 1/4-28, Thread Length: 15/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3M902C45A
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-185-2212
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N 3M902C4-5A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.469 Inches Nominal
Fastener Length:	0.765 Inches Minimum And 0.812 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.502 Inches Minimum And 0.507 Inches Maximum
Shoulder Diameter:	0.280 Inches Minimum First Shoulder And 0.281 Inches Maximum First Shoulder
Shoulder Length:	0.302 Inches Minimum First Shoulder And 0.322 Inches Maximum First Shoulder
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Shoulder Shape:	Round First Shoulder
Special Features:	Furnished With One O Ring. Must Be Lubricated With Cetyl Alcohol
Material:	Steel Comp Xm-13 Overall
Material Document And Classification:	Ams 5629 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3M902C4-5A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.