



Military-Fasteners.com

P/N 3M902C4-7A

Description

Fastener Length: 15/16", Thread: 1/4-28, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | 3M902C47A |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5305-01-142-8406 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N 3M902C4-7A Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.442 Inches Minimum And 0.509 Inches Maximum |
| Fastener Length: | 0.890 Inches Minimum And 0.937 Inches Maximum |
| Head Style: | Flat Countersunk Undercut |
| Head Diameter: | 0.502 Inches Minimum And 0.507 Inches Maximum |
| Head Height: | 0.058 Inches Minimum And 0.060 Inches Maximum |
| Shoulder Diameter: | 0.2802 Inches Minimum First Shoulder And 0.2807 Inches Maximum First Shoulder |
| Shoulder Length: | 0.368 Inches Minimum First Shoulder And 0.390 Inches Maximum First Shoulder |
| Internal Drive Style: | High-torque |
| Nominal Thread Diameter: | 0.250 Inches |
| Thread Quantity Per Inch: | 28 |
| Countersink Angle: | 100.0 Degrees Nominal |
| Shoulder Shape: | Round First Shoulder |
| Special Features: | Furnished With One Rubber O Ring |
| Material: | Steel Comp Xm-13 Overall |
| Material Document And Classification: | Ams5629 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3M902C4-7A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.