

Description

Fastener Length: 0-63/64", Thread: 1/4-24, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3M902C57A
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-190-2202
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N 3M902C5-7A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.531 Inches Nominal
Fastener Length:	0.953 Inches Minimum And 1.000 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.629 Inches Minimum And 0.634 Inches Maximum
Shoulder Diameter:	0.3427 Inches Minimum First Shoulder And 0.3432 Inches Maximum First Shoulder
Shoulder Length:	0.428 Inches Minimum First Shoulder And 0.448 Inches Maximum First Shoulder
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.312 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Shoulder Shape:	Round First Shoulder
Special Features:	Furnished With One O Ring. Must Be Lubricate With Cetyl Alcohol
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5629 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3M902C5-7A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.