

Description

Fastener Length: 0-63/64", Thread: 1/4-24, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | 3M902C57A |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5305-01-190-2202 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N 3M902C5-7A Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.531 Inches Nominal |
| Fastener Length: | 0.953 Inches Minimum And 1.000 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.629 Inches Minimum And 0.634 Inches Maximum |
| Shoulder Diameter: | 0.3427 Inches Minimum First Shoulder And 0.3432 Inches Maximum First Shoulder |
| Shoulder Length: | 0.428 Inches Minimum First Shoulder And 0.448 Inches Maximum First Shoulder |
| Internal Drive Style: | High-torque |
| Nominal Thread Diameter: | 0.312 Inches |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Countersink Angle: | 100.0 Degrees Nominal |
| Shoulder Shape: | Round First Shoulder |
| Special Features: | Furnished With One O Ring. Must Be Lubricate With Cetyl Alcohol |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5629 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3M902C5-7A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.