



Military-Fasteners.com

P/N 3M902C5-9A

Description

Fastener Length: 1-1/8", Thread: 1/4-24, Thread Length: 9/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3M902C59A
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-141-7195
Schedule B:	7318.16.0060
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N 3M902C5-9A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.506 Inches Minimum And 0.573 Inches Maximum
Fastener Length:	1.078 Inches Minimum And 1.125 Inches Maximum
Head Style:	Flat Countersunk Undercut
Head Diameter:	0.629 Inches Minimum And 0.634 Inches Maximum
Head Height:	0.075 Inches Minimum And 0.077 Inches Maximum
Shoulder Diameter:	0.3427 Inches Minimum First Shoulder And 0.3432 Inches Maximum First Shoulder
Shoulder Length:	0.475 Inches Minimum First Shoulder And 0.497 Inches Maximum First Shoulder
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.312 Inches
Thread Quantity Per Inch:	24
Countersink Angle:	100.0 Degrees Nominal
Shoulder Shape:	Round First Shoulder
Special Features:	Furnished With One Rubber O Ring
Material:	Steel Comp Xm-13 Overall
Material Document And Classification:	Ams5629 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3M902C5-9A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.