



Military-Fasteners.com

P/N 3M925C3-11D

Description

Fastener Length: 1-3/32", Thread: 10-32, Thread Length: 25/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3M925C311D
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-102-8456
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N 3M925C3-11D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.381 Inches Minimum And 0.431 Inches Maximum
Fastener Length:	1.079 Inches Minimum And 1.109 Inches Maximum
Head Style:	Flat Countersunk Undercut
Head Diameter:	0.3765 Inches Minimum And 0.3813 Inches Maximum
Head Height:	0.0439 Inches Minimum And 0.0459 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.678 Inches Minimum And 0.698 Inches Maximum
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp Xm-13 Overall
Material Document And Classification:	Ams 5629 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall And Chromate Overall
Surface Treatment Document And Classification:	Mil-c-83488 Ty 2 Cl 3 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3M925C3-11D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.