

**Description**

Fastener Length: 1-15/64", Thread: 1/4-28, Thread Length: 31/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | 3M925C412A                                |
| Minimum Qty (MOQ):      | 1 EA                                      |
| NSN:                    | 5305-01-231-7416                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N 3M925C4-12A Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.444 Inches Minimum And 0.494 Inches Maximum                                   |
| <b>Fastener Length:</b>                               | 1.204 Inches Minimum And 1.234 Inches Maximum                                   |
| <b>Head Style:</b>                                    | Flat Countersunk Undercut   |
| <b>Head Diameter:</b>                                 | 0.502 Inches Minimum And 0.507 Inches Maximum                                   |
| <b>Head Height:</b>                                   | 0.071 Inches Minimum And 0.073 Inches Maximum                                   |
| <b>Grip Diameter:</b>                                 | 0.2485 Inches Minimum And 0.2495 Inches Maximum                                 |
| <b>Internal Drive Style:</b>                          | High-torque   |
| <b>Nominal Thread Diameter:</b>                       | 0.250 Inches  |
| <b>Grip Length:</b>                                   | 0.740 Inches Minimum And 0.760 Inches Maximum                                   |
| <b>Thread Quantity Per Inch:</b>                      | 28  |
| <b>Countersink Angle:</b>                             | 99.0 Degrees Minimum And 101.0 Degrees Maximum                                  |
| <b>Surface Finish:</b>                                | 32.0 Microinches Grip   |
| <b>Surface Finish:</b>                                | 32.0 Microinches Threads  |
| <b>Special Features:</b>                              | Assembled With One O-ring Per St7m251,fscm 76301; Lubricated With Cetyl Alcohol |
| <b>Material:</b>                                      | Steel Comp Xm-13 Overall  |
| <b>Material Document And Classification:</b>          | Ams5629 Assn Std Single Material Response Overall                               |
| <b>Surface Treatment:</b>                             | Aluminum And Chromate Overall   |
| <b>Surface Treatment Document And Classification:</b> | Mil-c-83488,type 2,class 3 Mil Spec Single Treatment Response Overall           |
| <b>Thread Series Designator:</b>                      | Unjf  |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3M925C4-12A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.