



Military-Fasteners.com

P/N 3M925C4-13A

Description

Fastener Length: 1-9/32", Thread: 1/4-28, Thread Length: 31/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3M925C413A
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-231-7417
Schedule B:	7318.15.2010
ECCN:	EAR99
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc



* See page 2 for technical characteristics

P/N 3M925C4-13A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.444 Inches Minimum And 0.494 Inches Maximum
Fastener Length:	1.266 Inches Minimum And 1.296 Inches Maximum
Head Style:	Flat Countersunk Undercut
Head Diameter:	0.502 Inches Minimum And 0.507 Inches Maximum
Head Height:	0.071 Inches Minimum And 0.073 Inches Maximum
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.802 Inches Minimum And 0.822 Inches Maximum
Thread Quantity Per Inch:	28
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Special Features:	Assembled With One O-ring Per St7m251,fscm 76301; Lubricated With Cetyl Alcohol
Material:	Steel Comp Xm-13 Overall
Material Document And Classification:	Ams5629 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum And Chromate Overall
Surface Treatment Document And Classification:	Mil-c-83488,type 2,class 3 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3M925C4-13A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.