

**Description**

Fastener Length: 55/64", Thread: 1/4-28, Thread Length: 13/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	3M925C46D
Minimum Qty (MOQ):	15 EA
NSN:	5305-01-102-7955
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N 3M925C4-6D Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.335 Inches Minimum And 0.415 Inches Maximum
<b>Fastener Length:</b>	0.829 Inches Minimum And 0.859 Inches Maximum
<b>Head Style:</b>	Flat Countersunk Undercut
<b>Head Diameter:</b>	0.5018 Inches Minimum And 0.5066 Inches Maximum
<b>Head Height:</b>	0.0713 Inches Minimum And 0.0733 Inches Maximum
<b>Grip Diameter:</b>	0.2485 Inches Minimum And 0.2495 Inches Maximum
<b>Internal Drive Style:</b>	High-torque
<b>End Item Identification:</b>	Aircraft,eagle F-15
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Grip Length:</b>	0.444 Inches Minimum And 0.494 Inches Maximum
<b>Thread Quantity Per Inch:</b>	28
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Surface Finish:</b>	32.0 Microinches Grip
<b>Surface Finish:</b>	32.0 Microinches Threads
<b>Material:</b>	Steel Comp Xm-13 Overall
<b>Material Document And Classification:</b>	Ams 5629 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Aluminum Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Mil-c-83488 Ty 2 Cl 3 Mil Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/3M925C4-6D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.