

**Description**

Fastener Length: 1-5/32", Thread: 1/4-24, Thread Length: 35/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	3M925C510A
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-110-9772
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N 3M925C5-10A Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.506 Inches Minimum And 0.556 Inches Maximum
<b>Fastener Length:</b>	1.141 Inches Minimum And 1.171 Inches Maximum
<b>Head Style:</b>	Flat Countersunk Undercut
<b>Head Diameter:</b>	0.629 Inches Minimum And 0.633 Inches Maximum
<b>Head Height:</b>	0.088 Inches Minimum And 0.090 Inches Maximum
<b>Grip Diameter:</b>	0.3110 Inches Minimum And 0.3120 Inches Maximum
<b>Internal Drive Style:</b>	High-torque
<b>Nominal Thread Diameter:</b>	0.312 Inches
<b>Grip Length:</b>	0.615 Inches Minimum And 0.635 Inches Maximum
<b>Thread Quantity Per Inch:</b>	24
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Surface Finish:</b>	32.0 Microinches Grip
<b>Surface Finish:</b>	32.0 Microinches Threads
<b>Special Features:</b>	Furnished With One O-ring
<b>Material:</b>	Steel Comp Xm-13 Overall
<b>Surface Treatment:</b>	Aluminum Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Mil-c-83488,type2,class 3 Mil Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3M925C5-10A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.