

Description

Fastener Length: 1-5/32", Thread: 1/4-24, Thread Length: 35/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | 3M925C510D |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-102-7957 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N 3M925C5-10D Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.506 Inches Minimum And 0.556 Inches Maximum |
| Fastener Length: | 1.141 Inches Minimum And 1.171 Inches Maximum |
| Head Style: | Flat Countersunk Undercut |
| Head Diameter: | 0.6287 Inches Minimum And 0.6335 Inches Maximum |
| Head Height: | 0.0878 Inches Minimum And 0.0898 Inches Maximum |
| Grip Diameter: | 0.3110 Inches Minimum And 0.3120 Inches Maximum |
| Internal Drive Style: | High-torque |
| Nominal Thread Diameter: | 0.312 Inches |
| Grip Length: | 0.615 Inches Minimum And 0.635 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Steel Comp Xm-13 Overall |
| Material Document And Classification: | Ams 5629 Assn Std Single Material Response Overall |
| Surface Treatment: | Aluminum Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Mil-c-83488 Ty 2 Cl 3 Mil Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3M925C5-10D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.