

Description

Fastener Length: 1-23/64", Thread: 1/4-24, Thread Length: 35/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3M925C513A
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-235-2025
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N 3M925C5-13A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.507 Inches Minimum And 0.557 Inches Maximum
Fastener Length:	1.329 Inches Minimum And 1.359 Inches Maximum
Head Style:	Flat Countersunk Undercut
Head Diameter:	0.629 Inches Minimum And 0.634 Inches Maximum
Head Height:	0.088 Inches Minimum And 0.090 Inches Maximum
Grip Diameter:	0.3110 Inches Minimum And 0.3120 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.802 Inches Minimum And 0.822 Inches Maximum
Thread Quantity Per Inch:	24
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Special Features:	Assembled With One O-ring Per St7m251,fscm 76301; Lubricated With Cetyl Alcohol
Material:	Steel Comp Xm-13 Overall
Material Document And Classification:	Ams5629 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall And Chromate Overall
Surface Treatment Document And Classification:	Mil-c-83488,type 2,class 3 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3M925C5-13A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.