

**Description**

Fastener Length: 1-7/64", Thread: 1/4-24, Thread Length: 35/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | 3M925C59A                                 |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5305-01-110-7905                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N 3M925C5-9A Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.507 Inches Minimum And 0.557 Inches Maximum                        |
| <b>Fastener Length:</b>                               | 1.079 Inches Minimum And 1.109 Inches Maximum                        |
| <b>Head Style:</b>                                    | Flat Countersunk Undercut  |
| <b>Head Diameter:</b>                                 | 0.629 Inches Minimum And 0.633 Inches Maximum                        |
| <b>Head Height:</b>                                   | 0.088 Inches Minimum And 0.090 Inches Maximum                        |
| <b>Grip Diameter:</b>                                 | 0.3110 Inches Minimum And 0.3120 Inches Maximum                      |
| <b>Internal Drive Style:</b>                          | High-torque  |
| <b>Nominal Thread Diameter:</b>                       | 0.312 Inches   |
| <b>Grip Length:</b>                                   | 0.552 Inches Minimum And 0.572 Inches Maximum                        |
| <b>Thread Quantity Per Inch:</b>                      | 24   |
| <b>Countersink Angle:</b>                             | 99.0 Degrees Minimum And 101.0 Degrees Maximum                       |
| <b>Surface Finish:</b>                                | 32.0 Microinches Grip  |
| <b>Surface Finish:</b>                                | 32.0 Microinches Threads   |
| <b>Special Features:</b>                              | Furnished With One O-ring  |
| <b>Material:</b>                                      | Steel Comp Xm-13 Overall   |
| <b>Surface Treatment:</b>                             | Aluminum Overall And Chromate Overall                                |
| <b>Surface Treatment Document And Classification:</b> | Mil-c-83488,type2,class 3 Mil Spec Single Treatment Response Overall |
| <b>Thread Series Designator:</b>                      | Unjf   |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/3M925C5-9A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.