



Military-Fasteners.com

P/N 3M925C6-11A

Description

Fastener Length: 1-7/64", Thread: 3/8-24, Thread Length: 41/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3M925C611A
Minimum Qty (MOQ):	5
NSN:	5305-01-508-2154
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



* See page 2 for technical characteristics

P/N 3M925C6-11A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.636 Inches Minimum And 0.646 Inches Maximum
Fastener Length:	1.079 Inches Minimum And 1.109 Inches Maximum
Head Style:	Flat Countersunk Undercut
Head Diameter:	0.7556 Inches Minimum And 0.7604 Inches Maximum
Head Height:	0.1147 Inches Minimum And 0.1167 Inches Maximum
Grip Diameter:	0.373 Inches Minimum And 0.374 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.678 Inches Minimum And 0.698 Inches Maximum
Thread Quantity Per Inch:	24
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Part Name Assigned By Controlling Agency:	Screw,close Tolerance-assembly, 100 Degree C'sunk Sealing Head, Hi-torque,cres (125 Ksi Fsu), lvd Aluminum Coated
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams 5629 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall
Surface Treatment Document And Classification:	Mil-c-83488, Type 2, Class 3 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3M925C6-11A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.