

**Description**

Fastener Length: 1-7/64", Thread: 3/8-24, Thread Length: 41/64

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	3M925C611A
Minimum Qty (MOQ):	5
NSN:	5305-01-508-2154
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi

NO IMAGE  
AVAILABLE

## P/N 3M925C6-11A Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.636 Inches Minimum And 0.646 Inches Maximum
<b>Fastener Length:</b>	1.079 Inches Minimum And 1.109 Inches Maximum
<b>Head Style:</b>	Flat Countersunk Undercut
<b>Head Diameter:</b>	0.7556 Inches Minimum And 0.7604 Inches Maximum
<b>Head Height:</b>	0.1147 Inches Minimum And 0.1167 Inches Maximum
<b>Grip Diameter:</b>	0.373 Inches Minimum And 0.374 Inches Maximum
<b>Internal Drive Style:</b>	High-torque
<b>Nominal Thread Diameter:</b>	0.375 Inches
<b>Grip Length:</b>	0.678 Inches Minimum And 0.698 Inches Maximum
<b>Thread Quantity Per Inch:</b>	24
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Surface Finish:</b>	32.0 Microinches Grip
<b>Surface Finish:</b>	32.0 Microinches Threads
<b>Part Name Assigned By Controlling Agency:</b>	Screw,close Tolerance-assembly, 100 Degree C'sunk Sealing Head, Hi-torque,cres (125 Ksi Fsu), lvd Aluminum Coated
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Material Document And Classification:</b>	Ams 5629 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Aluminum Overall
<b>Surface Treatment Document And Classification:</b>	Mil-c-83488, Type 2, Class 3 Mil Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3M925C6-11A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.