



Military-Fasteners.com

P/N 3M925C6-12A

Description

Fastener Length: 1-19/64", Thread: 3/8-24, Thread Length: 41/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3M925C612A
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-373-4839
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N 3M925C6-12A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.641 Inches Nominal
Fastener Length:	1.259 Inches Minimum And 1.306 Inches Maximum
Head Style:	Flat Countersunk Undercut
Head Diameter:	0.692 Inches Minimum And 0.763 Inches Maximum
Head Height:	0.1147 Inches Minimum And 0.1167 Inches Maximum
Grip Diameter:	0.3735 Inches Minimum And 0.3745 Inches Maximum
Single Shear Strength:	125000 Pounds Per Square Inch
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.624 Inches Minimum And 0.644 Inches Maximum
Features Provided:	Cetyl Alcohol Lubricant
Thread Quantity Per Inch:	24
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	32.0 Microinches Bearing Surface Of Head32.0 Microinches Grip32.0 Microinches Threads
Material:	Steel Comp Xm-13 Fastener
Material Document And Classification:	Ams 5629 Assn Std Single Material Response Fastener
Surface Treatment:	Aluminum Fastener And Chromate Fastener
Surface Treatment Document And Classification:	Mil-c-83488 Ty 2 Cl 3 Mil Spec Single Treatment Response Fastener
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3M925C6-12A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.