



Military-Fasteners.com

P/N 3M926-3DL5

Description

Fastener Length: 45/64", Thread: 10-32, Thread Length: 25/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3M9263DL5
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-217-2190
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N 3M926-3DL5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.381 Inches Minimum And 0.431 Inches Maximum
Fastener Length:	0.703 Inches Minimum And 0.733 Inches Maximum
Head Style:	Fillister Countersunk
Head Diameter:	0.2966 Inches Minimum And 0.3016 Inches Maximum
Head Height:	0.013 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Shank Unthreaded Hole Diameter:	0.070 Inches Minimum And 0.075 Inches Maximum First Hole
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Thread Quantity Per Inch:	32
Countersink Angle:	101.0 Degrees Nominal
Distance From Head Largest Bearing Surface To Shank Hole Center:	0.582 Inches Minimum And 0.622 Inches Maximum First Hole
Special Features:	Cetyl Alcohol Lubrication
Material:	Steel Comp Xm-13 Overall
Material Document And Classification:	Ams 5629 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum And Chromate Overall
Surface Treatment Document And Classification:	Mil-c-83488,type2,class 3 Mil Spec All Treatment Responses Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3M926-3DL5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.