

Description

Fastener Length: 45/64", Thread: 10-32, Thread Length: 25/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | 3M9263DL5 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-217-2190 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N 3M926-3DL5 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.381 Inches Minimum And 0.431 Inches Maximum |
| Fastener Length: | 0.703 Inches Minimum And 0.733 Inches Maximum |
| Head Style: | Fillister Countersunk |
| Head Diameter: | 0.2966 Inches Minimum And 0.3016 Inches Maximum |
| Head Height: | 0.013 Inches Maximum |
| Grip Diameter: | 0.1885 Inches Minimum And 0.1895 Inches Maximum |
| Shank Unthreaded Hole Diameter: | 0.070 Inches Minimum And 0.075 Inches Maximum First Hole |
| Internal Drive Style: | High-torque |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.302 Inches Minimum And 0.322 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Countersink Angle: | 101.0 Degrees Nominal |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 0.582 Inches Minimum And 0.622 Inches Maximum First Hole |
| Special Features: | Cetyl Alcohol Lubrication |
| Material: | Steel Comp Xm-13 Overall |
| Material Document And Classification: | Ams 5629 Assn Std Single Material Response Overall |
| Surface Treatment: | Aluminum And Chromate Overall |
| Surface Treatment Document And Classification: | Mil-c-83488,type2,class 3 Mil Spec All Treatment Responses Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3M926-3DL5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.