

**Description**

Fastener Length: 1-9/64", Thread: 10-32, Thread Length: 25/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	3M9263L12
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-105-9371
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N 3M926-3L12 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.381 Inches Minimum And 0.431 Inches Maximum
<b>Fastener Length:</b>	1.141 Inches Minimum And 1.171 Inches Maximum
<b>Head Style:</b>	Oval Countersunk
<b>Head Diameter:</b>	0.2966 Inches Minimum And 0.3016 Inches Maximum
<b>Grip Diameter:</b>	0.1885 Inches Minimum And 0.1895 Inches Maximum
<b>Internal Drive Style:</b>	High-torque
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	0.740 Inches Minimum And 0.760 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Countersink Angle:</b>	101.0 Degrees Nominal
<b>Material:</b>	Steel Comp Xm-13 Overall
<b>Material Document And Classification:</b>	Ams 5629 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Aluminum Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Mil-c-83488 Ty 2 Cl 3 Mil Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3M926-3L12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.