

Description

Fastener Length: 1-15/32", Thread: 10-32, Thread Length: 25/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | 3M9263L17 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-284-1392 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N 3M926-3L17 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.382 Inches Minimum And 0.432 Inches Maximum |
| Fastener Length: | 1.454 Inches Minimum And 1.484 Inches Maximum |
| Head Style: | Fillister Countersunk |
| Head Diameter: | 0.297 Inches Minimum And 0.302 Inches Maximum |
| Head Height: | 0.013 Inches Maximum |
| Grip Diameter: | 0.1885 Inches Minimum And 0.1895 Inches Maximum |
| Internal Drive Style: | High-torque |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 1.052 Inches Minimum And 1.072 Inches Maximum |
| Features Provided: | Cetyl Alcohol Lubricant |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Color: | White Top Of Head |
| Material: | Steel Comp Xm-13 Overall |
| Surface Treatment: | Aluminum Overall |
| Surface Treatment Document And Classification: | Mil-c-83488,type 2 Class 3 Mil Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3M926-3L17> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.