

Description

Fastener Length: 1-19/32", Thread: 10-32, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3M9263L19
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-399-6096
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N 3M926-3L19 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.406 Inches Nominal
Fastener Length:	1.588 Inches Minimum And 1.598 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.297 Inches Minimum And 0.302 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.190 Inches
Grip Length:	1.177 Inches Minimum And 1.197 Inches Maximum
Features Provided:	Cetyl Alcohol Lubricant
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 100.0 Degrees Maximum
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Aluminum Overall
Surface Treatment Document And Classification:	Mil-c-83488,ty 2, Cl 3 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3M926-3L19> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.