

Description

Fastener Length: 1-11/64", Thread: 1/4-28, Thread Length: 31/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3M9264L11
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-105-1143
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N 3M926-4L11 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.444 Inches Minimum And 0.494 Inches Maximum
Fastener Length:	1.142 Inches Minimum And 1.172 Inches Maximum
Head Style:	Oval Countersunk
Head Diameter:	0.3898 Inches Minimum And 0.3948 Inches Maximum
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.678 Inches Minimum And 0.698 Inches Maximum
Thread Quantity Per Inch:	28
Countersink Angle:	101.0 Degrees Nominal
Material:	Steel Comp Xm-13 Overall
Material Document And Classification:	Ams 5629 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall And Chromate Overall
Surface Treatment Document And Classification:	Mil-c-83488 Ty 2 Cl 3 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3M926-4L11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.