



Military-Fasteners.com

P/N 3M926-4L2

Description

Fastener Length: 39/64", Thread: 1/4-28, Thread Length: 31/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3M9264L2
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-136-5749
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N 3M926-4L2 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.444 Inches Minimum And 0.494 Inches Maximum
Fastener Length:	0.579 Inches Minimum And 0.609 Inches Maximum
Head Style:	Oval Countersunk
Head Diameter:	0.390 Inches Minimum And 0.395 Inches Maximum
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Internal Drive Style:	High-torque
End Item Identification:	Aircraft,eagle F-15;f/a-18 Hornet
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.115 Inches Minimum And 0.135 Inches Maximum
Thread Quantity Per Inch:	28
Countersink Angle:	101.0 Degrees Nominal
Material:	Steel Comp Xm-13 Overall
Material Document And Classification:	23-112,fscm 76301 Mfr Ref Single Material Response Overall
Surface Treatment:	Aluminum Overall And Chromate Overall
Surface Treatment Document And Classification:	Mil-c-83488 Type 2 Class 3 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3M926-4L2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.