

Description

Fastener Length: 49/64", Thread: 1/4-28, Thread Length: 29/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | 3M9264L5 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5305-01-101-3326 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N 3M926-4L5 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.444 Inches Minimum And 0.494 Inches Maximum |
| Fastener Length: | 0.766 Inches Minimum And 0.796 Inches Maximum |
| Head Style: | Oval Countersunk |
| Head Diameter: | 0.3898 Inches Minimum And 0.3948 Inches Maximum |
| Grip Diameter: | 0.2485 Inches Minimum And 0.2495 Inches Maximum |
| Internal Drive Style: | High-torque |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.302 Inches Minimum And 0.322 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Countersink Angle: | 101.0 Degrees Nominal |
| Special Features: | Cetyl Alcohol Application Per Mcair Ps 18015 |
| Material: | Steel Comp Xm-13 Overall |
| Material Document And Classification: | Ams 5629 Assn Std Single Material Response Overall |
| Surface Treatment: | Aluminum Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Mil-c-83488 Ty 2 Cl 3 Mil Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3M926-4L5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.