

## P/N 3M926-5L12

## **Description**

Fastener Length: 1-9/32", Thread: 1/4-24, Thread Length: 35/64"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: 3M9265L12

Minimum Qty (MOQ): 1 EA

NSN: 5305-01-096-7350

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



# P/N 3M926-5L12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.506 Inches Minimum And 0.556 Inches Maximum
Fastener Length:	1.266 Inches Minimum And 1.296 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.429 Inches Minimum And 0.477 Inches Maximum
Grip Diameter:	0.3110 Inches Minimum And 0.3120 Inches Maximum
Internal Drive Style:	High-torque
End Item Identification:	Harrier;aircraft, Eagle F-15
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.740 Inches Minimum And 0.760 Inches Maximum
Thread Quantity Per Inch:	24
Countersink Angle:	99.5 Degrees Minimum And 100.5 Degrees Maximum
Special Features:	Cetyl Alcohol Application Per Mil-I-87132,type 1,grade B
Material:	Steel Comp Xm-13 Overall
Material Document And Classification:	23-112 Fscm 76301 Mfr Ref Single Material Response Overall
Surface Treatment:	Aluminum Overall
Surface Treatment Document And Classification:	Mil-c-83488 Ty 2 Class 3 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

### **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/3M926-5L12">https://military-fasteners.com/screws/machine+screws/3M926-5L12</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.