

**Description**

Fastener Length: 1-35/64", Thread: 1/4-24, Thread Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	3M9265L17
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-452-2729
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N 3M926-5L17 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.531 Inches Nominal
<b>Fastener Length:</b>	1.506 Inches Minimum And 1.556 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.469 Inches Minimum And 0.474 Inches Maximum
<b>Grip Diameter:</b>	0.311 Inches Minimum And 0.312 Inches Maximum
<b>Internal Drive Style:</b>	High-torque
<b>End Item Identification:</b>	F-15s
<b>Nominal Thread Diameter:</b>	0.312 Inches
<b>Grip Length:</b>	1.050 Inches Minimum And 1.070 Inches Maximum
<b>Thread Quantity Per Inch:</b>	24
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Special Features:</b>	Cetyl Alcohol Lubricated
<b>Material:</b>	Steel Comp Xm-13 Overall
<b>Surface Treatment:</b>	Aluminum Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3M926-5L17> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.