

Description

Fastener Length: 1-35/64", Thread: 1/4-24, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3M9265L17
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-452-2729
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N 3M926-5L17 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.531 Inches Nominal
Fastener Length:	1.506 Inches Minimum And 1.556 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.469 Inches Minimum And 0.474 Inches Maximum
Grip Diameter:	0.311 Inches Minimum And 0.312 Inches Maximum
Internal Drive Style:	High-torque
End Item Identification:	F-15s
Nominal Thread Diameter:	0.312 Inches
Grip Length:	1.050 Inches Minimum And 1.070 Inches Maximum
Thread Quantity Per Inch:	24
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Special Features:	Cetyl Alcohol Lubricated
Material:	Steel Comp Xm-13 Overall
Surface Treatment:	Aluminum Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3M926-5L17> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.