



★ FASTENERS

Military-Fasteners.com

P/N 3M926-5L8

Description

Fastener Length: 1-1/32", Thread: 1/4-24, Thread Length: 35/64", 3M926 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3M9265L8
Minimum Qty (MOQ):	5
NSN:	5305-01-105-7222
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N 3M926-5L8 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.506 Inches Minimum And 0.556 Inches Maximum
Fastener Length:	1.016 Inches Minimum And 1.046 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.429 Inches Minimum And 0.477 Inches Maximum
Grip Diameter:	0.3110 Inches Minimum And 0.3120 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.490 Inches Minimum And 0.510 Inches Maximum
Thread Quantity Per Inch:	24
Countersink Angle:	101.0 Degrees Nominal
Material:	Steel Comp Xm-13 Overall
Material Document And Classification:	Ams 5629 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall And Chromate Overall
Surface Treatment Document And Classification:	Mil-c-83488 Ty 2 Cl 3 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3M926-5L8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.