

Description

Fastener Length: 1-1/32", Thread: 1/4-24, Thread Length: 35/64", 3M926 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | 3M9265L8 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5305-01-105-7222 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N 3M926-5L8 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.506 Inches Minimum And 0.556 Inches Maximum |
| Fastener Length: | 1.016 Inches Minimum And 1.046 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.429 Inches Minimum And 0.477 Inches Maximum |
| Grip Diameter: | 0.3110 Inches Minimum And 0.3120 Inches Maximum |
| Internal Drive Style: | High-torque |
| Nominal Thread Diameter: | 0.312 Inches |
| Grip Length: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Countersink Angle: | 101.0 Degrees Nominal |
| Material: | Steel Comp Xm-13 Overall |
| Material Document And Classification: | Ams 5629 Assn Std Single Material Response Overall |
| Surface Treatment: | Aluminum Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Mil-c-83488 Ty 2 Cl 3 Mil Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3M926-5L8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.