

**Description**

Fastener Length: 1-1/32", Thread: 1/4-24, Thread Length: 35/64", 3M926 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | 3M9265L8                                  |
| Minimum Qty (MOQ):      | 5   |
| NSN:                    | 5305-01-105-7222                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N 3M926-5L8 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.506 Inches Minimum And 0.556 Inches Maximum                    |
| <b>Fastener Length:</b>                               | 1.016 Inches Minimum And 1.046 Inches Maximum                    |
| <b>Head Style:</b>                                    | Flat Countersunk   |
| <b>Head Diameter:</b>                                 | 0.429 Inches Minimum And 0.477 Inches Maximum                    |
| <b>Grip Diameter:</b>                                 | 0.3110 Inches Minimum And 0.3120 Inches Maximum                  |
| <b>Internal Drive Style:</b>                          | High-torque  |
| <b>Nominal Thread Diameter:</b>                       | 0.312 Inches   |
| <b>Grip Length:</b>                                   | 0.490 Inches Minimum And 0.510 Inches Maximum                    |
| <b>Thread Quantity Per Inch:</b>                      | 24   |
| <b>Countersink Angle:</b>                             | 101.0 Degrees Nominal  |
| <b>Material:</b>                                      | Steel Comp Xm-13 Overall   |
| <b>Material Document And Classification:</b>          | Ams 5629 Assn Std Single Material Response Overall               |
| <b>Surface Treatment:</b>                             | Aluminum Overall And Chromate Overall                            |
| <b>Surface Treatment Document And Classification:</b> | Mil-c-83488 Ty 2 Cl 3 Mil Spec Single Treatment Response Overall |
| <b>Thread Series Designator:</b>                      | Unjf   |

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3M926-5L8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.