

Description

Fastener Length: 1-9/32", Thread: 3/8-24, Thread Length: 21/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3M9266L10
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-101-8538
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N 3M926-6L10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.616 Inches Minimum And 0.666 Inches Maximum
Fastener Length:	1.251 Inches Minimum And 1.281 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.510 Inches Minimum And 0.564 Inches Maximum
Grip Diameter:	0.3735 Inches Minimum And 0.3745 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Thread Quantity Per Inch:	24
Countersink Angle:	101.0 Degrees Nominal
Material:	Steel Comp Xm-13 Overall
Material Document And Classification:	Ams 5629 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall And Chromate Overall
Surface Treatment Document And Classification:	Mil-c-83488 Ty 2 Cl 3 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3M926-6L10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.