

**Description**

Fastener Length: 1-3/32", Thread: 3/8-24, Thread Length: 21/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	3M9266L7
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-209-7200
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N 3M926-6L7 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.616 Inches Minimum And 0.666 Inches Maximum
<b>Fastener Length:</b>	1.064 Inches Minimum And 1.094 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.510 Inches Minimum And 0.564 Inches Maximum
<b>Grip Diameter:</b>	0.3735 Inches Minimum And 0.3745 Inches Maximum
<b>Internal Drive Style:</b>	High-torque
<b>Nominal Thread Diameter:</b>	0.375 Inches
<b>Grip Length:</b>	0.428 Inches Minimum And 0.448 Inches Maximum
<b>Thread Quantity Per Inch:</b>	24
<b>Countersink Angle:</b>	101.0 Degrees Nominal
<b>Special Features:</b>	With Cetyl Alcohol Per Mil-I-87132,ty1,grb As A Lubricant
<b>Material:</b>	Steel Comp Xm-13 Overall
<b>Material Document And Classification:</b>	Ams5629 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Aluminum And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Mil-c-83488,ty2,cl3 Mil Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3M926-6L7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.