

## **P/N 3SLC-C10**

### **Description**

Collar part number

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

# Order this part online

#### **Additional Information**

| SKU / Model:            | 3SLCC10               |
|-------------------------|-----------------------|
| Minimum Qty (MOQ):      | 25 EA                 |
| NSN:                    | 5320-01-329-6720      |
| Schedule B:             | 7616.10.1000          |
| ECCN:                   | 9A991                 |
| National Motor Freight: | 095190, Hardware, Noi |



<sup>\*</sup> See page 2 for technical characteristics

## **P/N 3SLC-C10 Specifications**

| Collar Outside Diameter:                       | 0.444 Inches Minimum And 0.448 Inches Maximum                   |
|--|---|
| Collar Overall Height:                         | 0.324 Inches Minimum And 0.344 Inches Maximum                   |
| Collar Inside Diameter:                        | 0.310 Inches Minimum And 0.314 Inches Maximum                   |
| Collar Style:                                  | Straight Type   |
| Special Features:                              | Chamfered Ends,20 Degrees                                       |
| Material:                                      | Aluminum Alloy 2024 Overall                                     |
| Material Document And Classification:          | Qq-a-430 Fed Spec Single Material Response Overall              |
| Surface Treatment:                             | Anodize Overall   |
| Surface Treatment Document And Classification: | Mil-a-8625,ty 2,cl 2 Mil Spec Single Treatment Response Overall |

### **How to Order**

Order this collar from our inventory online by visiting <a href="https://military-fasteners.com/collars/pin\_rivet+collars/3SLC-C10">https://military-fasteners.com/collars/pin\_rivet+collars/3SLC-C10</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.