

P/N 3SLC-C12

Description

anodize aluminum alloy, 3SLC series collar

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: 3SLCC12

Minimum Qty (MOQ): 25

NSN: 5320-01-331-1339

Schedule B: 7616.10.1000

ECCN: EAR99

National Motor Freight: 095190, Hardware, Noi



^{*} See page 2 for technical characteristics

P/N 3SLC-C12 Specifications

Collar Outside Diameter:	0.529 Inches Minimum And 0.533 Inches Maximum
Collar Overall Height:	0.364 Inches Minimum And 0.384 Inches Maximum
Collar Inside Diameter:	0.374 Inches Minimum And 0.378 Inches Maximum
Collar Style:	Straight Type
Special Features:	Chamfered Ends,20 Degrees
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty 2,cl 2 Mil Spec Single Treatment Response Overall

How to Order

Order this collar from our inventory online by visiting https://military-fasteners.com/collars/collars/3SLC-C12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/collars/collars/3SLC-C12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/collars/collars/3SLC-C12 and selecting the quantity you want then click "add to cart".