

**Description**

Fastener Length: 5/8", Thread: 6-32, Thread Length: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	3V107610
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-462-9734
Schedule B:	7318.15.6080
ECCN:	EAR99

NO IMAGE  
AVAILABLE

## P/N 3V1076-10 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.253 Inches Nominal
<b>Fastener Length:</b>	0.595 Inches Minimum And 0.635 Inches Maximum
<b>Head Style:</b>	Pan No. 2
<b>Head Diameter:</b>	0.256 Inches Minimum And 0.270 Inches Maximum
<b>Head Height:</b>	0.087 Inches Minimum And 0.097 Inches Maximum
<b>First Diameter From Head:</b>	0.084 Inches Minimum And 0.089 Inches Maximum
<b>Distance From Largest Bearing Surface Of Head To End Of First Diameter:</b>	0.362 Inches Minimum And 0.382 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.138 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Externally Relieved Body Diameter Quantity:</b>	1
<b>Color:</b>	Black Overall
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Material Document And Classification:</b>	Qq-s-763 300 Series Fed Spec All Material Responses Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3V1076-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.