

Description

Fastener Length: 5/8", Thread: 6-32, Thread Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3V107610
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-462-9734
Schedule B:	7318.15.6080
ECCN:	EAR99



* See page 2 for technical characteristics

P/N 3V1076-10 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.253 Inches Nominal
Fastener Length:	0.595 Inches Minimum And 0.635 Inches Maximum
Head Style:	Pan No. 2
Head Diameter:	0.256 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.087 Inches Minimum And 0.097 Inches Maximum
First Diameter From Head:	0.084 Inches Minimum And 0.089 Inches Maximum
Distance From Largest Bearing Surface Of Head To End Of First Diameter:	0.362 Inches Minimum And 0.382 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Externally Relieved Body Diameter Quantity:	1
Color:	Black Overall
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Qq-s-763 300 Series Fed Spec All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3V1076-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.