

Description

corrosion resistant steel - slotted recess - total panel thickness 0.321" - 0.350"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	400211S
Minimum Qty (MOQ):	1
NSN:	5325-00-727-9945
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



P/N 4002-11S Specifications

Diameter:	0.377 Inches Minimum And 0.384 Inches Maximum
Turnlock Stud Head Style:	Flat Countersunk
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.723 Inches Minimum And 0.733 Inches Maximum
Eyelet Outside Diameter:	0.341 Inches Minimum And 0.348 Inches Maximum
Eyelet Length:	0.472 Inches Nominal
Material Accommodated Thickness:	0.351 Inches Minimum And 0.380 Inches Maximum
Drive Type:	Slotted
Material:	Steel Comp 302 Ejector Spring
Material:	Steel Comp 302 Stud
Material:	Steel Comp 302 Pin
Material:	Steel Comp 305 Eyelet
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/4002-11S> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.