P/N 4002-12

Description

Diameter: 3/8", steel overall

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: 400212

Minimum Qty (MOQ): 10

NSN: 5325-00-639-5061

Schedule B: 7318.29.0000

ECCN: EAR99

National Motor Freight: 093490, Bolt / Nut / Screw / Clips / Fastener / Etc









P/N 4002-12 Specifications

Diameter:	0.377 Inches Minimum And 0.384 Inches Maximum
Turnlock Stud Head Style:	Flat Countersunk
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.753 Inches Minimum And 0.763 Inches Maximum
Eyelet Outside Diameter:	0.341 Inches Minimum And 0.348 Inches Maximum
Eyelet Length:	0.502 Inches Nominal
Material Accommodated Thickness:	0.381 Inches Minimum And 0.410 Inches Maximum
Drive Type:	Slotted
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/4002-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/4002-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/4002-12 and selecting the quantity you want then click "add to cart".