

**Description**

1/4 turn, camloc, cadmium, 4002 series stud

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	400214
Minimum Qty (MOQ):	5
NSN:	5325-00-639-5042
Schedule B:	7318.29.0000
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



\* See page 2 for technical characteristics

## P/N 4002-14 Specifications

<b>Diameter:</b>	0.380 Inches Nominal
<b>Securing Device Type:</b>	Washer
<b>Turnlock Stud Head Style:</b>	Flat Countersunk
<b>Stud Assembly Style:</b>	Stud Assembly
<b>Distance From Engaging Member To Largest Bearing Surface Of Head:</b>	0.813 Inches Minimum And 0.823 Inches Maximum
<b>Eyelet Outside Diameter:</b>	0.341 Inches Minimum And 0.348 Inches Maximum
<b>Eyelet Length:</b>	0.562 Inches Nominal
<b>Material Accommodated Thickness:</b>	0.441 Inches Minimum And 0.460 Inches Maximum
<b>Drive Type:</b>	Slotted
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall

## How to Order

Order this turnlock fastener stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+studs/4002-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.