

Description

4002-15SW Turnlock Fastener Stud Assembly

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	400215SW
Minimum Qty (MOQ):	2
NSN:	5325-00-923-4336
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



NO IMAGE
AVAILABLE

P/N 4002-15SW Specifications

Head Length:	0.850 Inches Minimum And 0.890 Inches Maximum
Turnlock Stud Head Style:	Flat Countersunk Wing
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.843 Inches Minimum And 0.858 Inches Maximum
Eyelet Outside Diameter:	0.341 Inches Minimum And 0.348 Inches Maximum
Eyelet Length:	0.592 Inches Nominal
Material Accommodated Thickness:	0.471 Inches Minimum And 0.500 Inches Maximum
Material:	Steel Comp 302 Ejector Spring
Material:	Steel Comp 302 Stud
Material:	Steel Comp 302 Head
Material:	Steel Comp 302 Pin
Material:	Steel Comp 305 Eyelet
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/4002-15SW> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.