

P/N 4002-15W

Description

1/4 Turn Stud

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: 400215W

Minimum Qty (MOQ):

NSN: 5325-00-624-9931

Schedule B: 7318.15.5030

ECCN: 9A991

National Motor Freight: 066440, Fasteners Curtain / Snap Metal

NO IMAGE AVAILABLE

^{*} See page 2 for technical characteristics

P/N 4002-15W Specifications

| Head Length: | 0.850 Inches Minimum And 0.890 Inches Maximum |
|---|--|
| Turnlock Stud Head Style: | Flat Countersunk Wing |
| Stud Assembly Style: | Stud Assembly |
| Distance From Engaging Member To Largest Bearing Surface Of Head: | 0.843 Inches Minimum And 0.858 Inches Maximum |
| Eyelet Outside Diameter: | 0.344 Inches Nominal |
| Eyelet Length: | 0.592 Inches Nominal |
| Material Accommodated Thickness: | 0.471 Inches Minimum And 0.500 Inches Maximum |
| Material: | Steel Comp 1009 Eyelet Or Steel Comp 1050 Eyelet Or Steel Comp 1112 Eyelet |
| Material: | Steel Comp 1009 Head |
| Material: | Steel Comp 4037 Stud |
| Material: | Steel Ejector Spring |
| Material: | Steel Pin |
| Material Document And Classification: | Qq-w-470 Fed Spec Single Material Response Ejector Spring |
| Material Document And Classification: | Qq-w-470 Fed Spec Single Material Response Pin |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec All Treatment Responses Overall |

How to Order

Order this turnlock fastener eyelet from our inventory online by visiting https://military-fasteners.com/studs/turnlock+fastener+eyelets/4002-15W and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/studs/turnlock+fastener+eyelets/4002-15W and selecting the