

Description

Diameter: 3/8", steel comp 305 eyelet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	400216S
Minimum Qty (MOQ):	5 EA
NSN:	5325-00-078-7560
Schedule B:	7318.15.5030
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



* See page 2 for technical characteristics

P/N 4002-16S Specifications

Diameter:	0.380 Inches Nominal
Turnlock Stud Head Style:	Flat Countersunk
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.843 Inches Minimum And 0.873 Inches Maximum
Eyelet Outside Diameter:	0.341 Inches Minimum And 0.348 Inches Maximum
Eyelet Length:	0.257 Inches Nominal
Material Accommodated Thickness:	0.501 Inches Minimum And 0.530 Inches Maximum
Drive Type:	Slotted
Material:	Steel Comp 302 Ejector Spring
Material:	Steel Comp 302 Stud
Material:	Steel Comp 302 Pin
Material:	Steel Comp 305 Eyelet
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

How to Order

Order this 1/4 turn stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+eyelets/4002-16S> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.