

Description

cadmium plated steel, slotted recess, total panel thickness: 0.081" - 0.11",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[1142000-3](#)

| | |
|--------------------|------------------|
| SKU / Model: | 40023 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5325-00-639-4889 |
| ECCN: | EAR99 |



* See page 2 for technical characteristics

P/N 4002-3 Specifications

| | |
|--|---|
| Diameter: | 0.377 Inches Minimum And 0.384 Inches Maximum |
| Turnlock Stud Head Style: | Flat Countersunk |
| Stud Assembly Style: | Stud Assembly |
| Distance From Engaging Member To Largest Bearing Surface Of Head: | 0.483 Inches Minimum And 0.493 Inches Maximum |
| Eyelet Outside Diameter: | 0.341 Inches Minimum And 0.348 Inches Maximum |
| Eyelet Length: | 0.257 Inches Nominal |
| Material Accommodated Thickness: | 0.110 Inches Minimum And 0.140 Inches Maximum |
| Drive Type: | Slotted |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/4002-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.